



Pin	Symbol
1	C1N
2	C1P
3	C2P
4	C2N
5	VDD2
6	IREF
7	VCOMH
8	VPP
9	VSL
10	VCC
11	VDD1
12	GPIO
13	IM0
14	IM1
15	IM2
16	V1_OPT
17	GND
18	FT0
19	FT1
20	VPPS
21	GND
22	CSB
23	RESB
24	RS
25	WRB
26	RDB
27	D0
28	D1
29	D2
30	D3
31	D4
32	D5
33	D6
34	D7
35	GND

Notes:

1. Color: Yellow
2. Driver IC: KS0066 equivalent
3. FPC Number: UT-0111-P01
4. Interface: 4-/8-bit 68XX/80XX Parallel, SPI, I2C
5. General Tolerance: ±0.30
6. The total thickness (2.10 Max) is without polarizer protective film & remove tape.  
The actual assembled total thickness with above materials should be 2.35 Max.

日期	版本	修改内容	晶發科技股份有限公司 GI FAR TECHNOLOGY CO., LTD			
			DATE	2018.10.22	REV	X0
			UNIT : mm	Product :	GFOC1602AA-YG	
			SCALE : 1 / 1	DRAWN :	Hazel	CHECKED : Sidney
			SHEET : 1 / 1			PAGE : 1 / 1